



Lecol 5500

Adhesive

- ▶ HIGH INITIAL GRAB
- ▶ SUITABLE FOR UNDERFLOOR HEATING SYSTEMS
- ▶ SUITABLE FOR ALL TYPES OF WOOD FLOORING
- ▶ SUITABLE FOR USE WITH WATERBORNE LACQUERS
- ▶ VERY GOOD FILLING PROPERTIES
- ▶ VERY STRONG ADHESION
- ▶ WATER FREE





the new generation

Lecol 5500

Adhesive

APPLICATION:

Lecol Leads with Lecol 5500, an Alcohol based adhesive for use with all types of wood flooring on absorbent and non-absorbent sub-floors. With Lecol 5500 the high initial grab is unrivalled and together with its very good filling properties makes Lecol 5500 the ideal adhesive for installing large floor elements. Lecol 5500 can also be used to install pre-finished wood flooring.

Lecol 5500 is a solid adhesive limiting the movement of the wood due to expansion and contraction as the room climate conditions change. The use of a solid adhesive is essential when finishing the floor with a waterborne lacquer. This contributes to the long life span of the floor and limits the hollow sound of footsteps.

PREPARATION:

The correct preparation of the subfloor is very important when choosing an adhesive for wood flooring. Floors must be sound, clean and dust free. Levelling compounds must be used where necessary and the floors correctly primed to ensure a better bond between the adhesive and the sub-floor. Some primers can be used as a Damp Proof Membrane.

Lecol K495 can be used to prime the subfloor prior to the application of Lecol 5500 to increase the structural strength of the subfloor and provide a better bond to the adhesive.

Lecol PU235 can be used to prime the subfloor and create a Damp Proof Membrane prior to application of Lecol 5500. Sharp-grit S28 MUST be scattered on the final coat of Lecol PU235 to ensure adhesion with Lecol 5500 (see PU235 application method)



SIZES:

Lecol 5500 is available in 3 sizes

- 16Kg
- 10Kg
- 6Kg

CONSUMPTION:

approx. 700-900 g/m²
(depending on the structure of subfloor).

ADDITIONAL INFORMATION:

See technical data sheet.



Lecol Chemie b.v.
Postbox 51 NL-5140 AB
Waalwijk, The Netherlands
Tel.: 0870 922 2837
Fax. : +31 416 566 531
saleslecol@lecol.nl
www.lecol.nl

